



KOSTER BD Outside Corner

Technical Data Sheet B 933 001

Issued: 03-28-24

Elastic formed material for waterproofing outside corners with KOSTER BD 50 Waterproofing Systems under tile

Features

KOSTER BD Outside Corner is made of nitril butadiene rubber (NBR) and is reinforced with an overlaying mesh. It is designed for permanent elastic waterproofing of wet rooms as part of the KOSTER BD Waterproofing System.

Technical Data

Resistance to temperature
Leg Length

-4 - 194°F
2.36 inches

Fields of Application

KOSTER BD Outside Corner is a system component for the permanent waterproofing of corners under ceramic coverings. As part of the KOSTER BD System, the KOSTER BD Outside Corner is used as a flexible waterproofing form piece embedded into KOSTER BD 50.

Substrate

The substrate must be sound, solid, dry, and free of dust and grease.

Application

Prime the substrate with KOSTER BD 50 Primer. After 3 hours, apply the first layer of KOSTER BD 50. Embed KOSTER BD Outside Corner into the fresh coat of KOSTER BD 50 on outside corners. After the first layer has dried, apply the second layer of KOSTER BD 50. Coat over the mesh on the edges of the KOSTER BD Outside Corner so the outside corner is completely connected to the waterproofed area.

Packaging

B 933 001 piece

Safety

Consult Safety Data Sheet. Always wear proper personal protective equipment when handling this product.

Limited Warranty

KOSTER warrants that its product shall be in accordance with the specifications published in the current revision of the products data sheet. KOSTER covenants that in the event any of its products fail to meet their published specifications, KOSTER shall replace those products proved to be defective. KOSTER shall not be responsible for any incidental or consequential damages due to the breach of its warranties. Notwithstanding the foregoing, KOSTER's sole liability hereunder shall not exceed the cost of the defective product originally purchased. EXCEPT AS SET FORTH ABOVE, KOSTER MAKES NO OTHER WARRANTIES EXPRESS OR IMPLIED AND MAKES NO WARRANTY AS TO THE MERCHANTABILITY OR FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON

THE FACE HEREOF. The user must determine if the product is suited for the intended use and the user must bear the risks and liabilities associated with it.

Related products

KOSTER BD 50 Primer	Art.-Nr. B 190 005
KOSTER BD 50	Art.-Nr. B 290 010
KOSTER BD Flexible Tile Adhesive	Art.-Nr. B 540 025
KOSTER BD Flex Tape K 120	Art.-Nr. B 931
KOSTER BD Inside Corner	Art.-Nr. B 932 001
KOSTER BD Wall Sleeve	Art.-Nr. B 934 001
KOSTER BD Floor Sleeve	Art.-Nr. B 935 001

Art.-Nr. B 190 005
Art.-Nr. B 290 010
Art.-Nr. B 540 025
Art.-Nr. B 931
Art.-Nr. B 932 001
Art.-Nr. B 934 001
Art.-Nr. B 935 001

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The installer is responsible for the correct application taking into consideration the specific conditions of the construction site and the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which deviate from the specifications contained in any Company literature may not be relied upon in the absence of written confirmation from the Company. The installer must comply with all testing, technical requirement, guidelines, and industry customs at all times. The terms, conditions, and limitations contained in the written warranty for the product controls over the specifications contained herein. This guideline has been technically revised: all previous versions are invalid.

KOSTER AMERICAN CORPORATION | 2585 Aviator Drive | Virginia Beach, VA 23453
Phone (757) 425-1206 | Fax (757) 425-9951 | info@kosterusa.com | www.kosterusa.com