



Technical Data Sheet J 981 001

Issued: 04-30-19

KOSTER Special Caulking Gun

Caulking gun for installing KOSTER KB-Flex 200

Features

KOSTER Special Caulking Gun is a tool for application of KOSTER KB-Flex® 200 Sealing Paste.

Application

Prior to the application of KOSTER KB-Flex® 200 Sealing Paste, the cartridge is placed in warm water and brought to a temperature of about 86°F. This temperature ensures that the material will have the optimal consistency for application. The KOSTER KB-Flex® 200 cartridge is then placed in the KOSTER Special Caulking Gun and the material is pressed into the penetration from the back to front.

Packaging

J 981 001

piece

Safety

Consult Safety Data Sheet. Always wear proper personal protective equipment.

Limited Warranty

KOSTER warrants that its product shall be in accordance with the specifications published in the current revision of the products data sheet. KOSTER covenants that in the event any of its products fail to meet their published specifications, KOSTER shall replace those products proved to be defective. KOSTER shall not be responsible for any incidental or consequential damages due to the breach of its warranties. Notwithstanding the foregoing, KOSTER's sole liability hereunder shall not exceed the cost of the defective product originally purchased. EXCEPT AS SET FORTH ABOVE, KOSTER MAKES NO OTHER WARRANTIES EXPRESS OR IMPLIED AND MAKES NO WARRANTY AS TO THE MERCHANTABILITY OR FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The user must determine if the product is suited for the intended use and the user must bear the risks and liabilities associated with it.

Related products

KOSTER Cleaning Brush
KOSTER KB-Flex 200

Art.-Nr. IN 959 001 Art.-Nr. J 250

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The installer is responsible for the correct application taking into consideration the specific conditions of the construction site and the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which deviate from the specifications contained in any Company literature may not be relied upon in the absence of written confirmation from the Company. The installer must comply with all testing, technical requirement, guidelines, and industry customs at all times. The terms, conditions, and limitations contained in the written warranty for the product controls over the specifications contained herein. This guideline has been technically revised; all previous versions are invalid.