



KOSTER Universal Cleaner

Technical Data Sheet X 910 010

Issued: 12-22-16

Solvent free cleaning agent for bituminous materials and epoxy resins

Features

KOSTER Universal Cleaner dissolves and removes soft and partially cured bituminous materials and epoxy resins.

Fields of Application

For cleaning tools and machines that have been soiled with bitumen or epoxy materials. Do not use for cleaning of polyurethane-based materials.

Application

Clean tools and machines immediately after use with KOSTER Universal Cleaner.

When cleaning heavily soiled tools and parts, clean with a brush or cloth. Parts and tools can also be placed in a KOSTER Universal Cleaner bath to soak and soften encrusted material before cleaning.

Packaging

X 910 010 2.64 gal jerrycan

Storage

Store the material frost free.

Safety

Consult Safety Data Sheet. Always wear proper personal protective equipment when handling this product.

Limited Warranty

KOSTER warrants that its product shall be in accordance with the specifications published in the current revision of the products data sheet. KOSTER covenants that in the event any of its products fail to meet their published specifications, KOSTER shall replace those products proved to be defective. KOSTER shall not be responsible for any incidental or consequential damages due to the breach of its warranties. Notwithstanding the foregoing, KOSTER's sole liability hereunder shall not exceed the cost of the defective product originally purchased. EXCEPT AS SET FORTH ABOVE, KOSTER MAKES NO OTHER WARRANTIES EXPRESS OR IMPLIED AND MAKES NO WARRANTY AS TO THE MERCHANTABILITY OR FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The user must determine if the product is suited for the intended use and the user must bear the risks and liabilities associated with it.

Related products

KOSTER ORS D
KOSTER VAP I 2000 Zero VOC
KOSTER Corrosion Protection
KOSTER Bridge Coat
KOSTER KB-Pox Adhesive
KOSTER CFR 1
KOSTER KBE Liquid Film
KOSTER Deuxan Professional

Art.-Nr. CT 138 010
Art.-Nr. CT 230
Art.-Nr. CT 283 006
Art.-Nr. CT 284
Art.-Nr. J 120 005
Art.-Nr. W 220 023
Art.-Nr. W 245
Art.-Nr. W 256 032

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The installer is responsible for the correct application taking into consideration the specific conditions of the construction site and the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which deviate from the specifications contained in any Company literature may not be relied upon in the absence of written confirmation from the Company. The installer must comply with all testing, technical requirement, guidelines, and industry customs at all times. The terms, conditions, and limitations contained in the written warranty for the product controls over the specifications contained herein. This guideline has been technically revised; all previous versions are invalid.

KOSTER AMERICAN CORPORATION | 2585 Aviator Drive | Virginia Beach, VA 23453
Phone (757) 425-1206 | Fax (757) 425-9951 | info@kosterusa.com | www.kosterusa.com